

3 inch re-stick label paper

SK1-311 Re-stick

Kiosk printer for linerless labels

- Max.200mm/sec printing
- Linerless and re-stick (re-positional) media support
- No need to peel off liner paper from the label
- Eco friendly thanks to linerless
- Auto paper cutter incorporated
- Ideal for installation into Kiosk terminals



Application examples

Food label



- No waste thanks to linerless label
- Print many labels first, then paste them on several positions as the labels are re-positional

Kitchen



- Put on ordered meal and can remove quickly when serving

Logistic



- No waste even when many labels are printed
- Remove quickly when the new label needs to be put (no glue left on the cartons after removing)

Basic Specifications

| SK1-311 Re-stick | |
|-----------------------|---|
| Printing method | Direct line thermal |
| Dot density | 203dpi (8dot/mm) |
| Print width | 80mm/83mm |
| Print speed | Max.200 mm/sec |
| Paper roll | Paper width : 80mm/83mm Paper roll diameter : Φ83mm Recommended media : MAXStick X2,Plus,2Go,Premium |
| Barcode | UPC-A/E, JAN13/8, CODE39, ITF, CODABAR, CODE128, GS1 Databar Omni-directional, Truncated, Limited, Stacked, Stacked Omni-directional QR, MicroQR, MaxiCode, MicroPDF417, PDF417, DataMatrix |
| Auto paper cutter | Partial / Full cut |
| Power supply | DC24V |
| Interface | USB & Serial (RS-232) |
| Command system | ESC/POS compatible (*1) |
| Operating environment | 5 to 34 °C 10% to 80%RH (non-condensing) |
| Storage environment | -20 to 60 °C 20% to 85%RH (non-condensing) |
| Reliability | Thermal head : 100km or more Cutter : 1M cuts or more (with recommended paper) |
| Dimensions | 127(W) × 129.2(D) × 73.6(H)mm |
| Weight | Approx. 630g (without paper roll) |
| Safety regulatory | CE, FCC, VCCI(Class A) / RoHS/ UL |
| Maintenance cycle | Recommended : 10 Rolls/Thermal head, 0.1M cuts/cutter (*2) |
| Price | Please ask |

(*1) ESC/POS is registered trademark of Seiko Epson Corporation.

(*2)For the cleaning, please refer to our product guide.